

## 3 - Circuit Protection& Industrial Control





## AC3086

## **Plastic Consumer Unit Relocation box**

## **Features and benefits**

**Material Polycarbonate** 

**Protection class IP65** 

Temp. range min -25 °C

Temp. range max 85 °C

Glow wire test 650 °C

Impact resistance IK08

External dimensions LxWxH 215x200x95mm

Suitable f<mark>or relocating up to 10 wa</mark>ys\*

Fast self-tapping stainless screws

Technical Specification		
Attribute	<b>Value</b>	

\*Each Final ring circuit need to be considered as 2 ways

2102-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm
2102-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1207 - Green/Yellow 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1292 - Orange Endplate for 2102

2110-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm

2110-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm  $\,$ 

 ${\bf 2110\text{-}1207\text{-}Green/Yellow\,2\,conductor\,DIN\text{-}rail\,terminal\,with\,Lever\,and\,push\text{-}in\,up\,to\,16mm}$ 

2110-1292 - Orange Endplate for 2110

3-AC3086-2022-V1

