



### AC3087

### Plastic Consumer Unit Relocation box

#### Features and benefits

**Material Polycarbonate**

**Protection class IP65**

**Temp. range min -25 °C**

**Temp. range max 85 °C**

**Glow wire test 650 °C**

**Impact resistance IK08**

**External dimensions LxWxH 270x250x160mm**

**Suitable for relocating up to 20 ways\***

**Fast self-tapping stainless screws**

\*Each Final ring circuit need to be considered as 2 ways

Terminals\*\*

2202-1201 - Grey 2 conductor DIN-rail terminal with button push-in up to 4mm (x16)

2202-1204 - Blue 2 conductor DIN-rail terminal with button push-in up to 4mm (x16)

2202-1207 - Green/Yellow 2 conductor DIN-rail terminal with button push-in up to 4mm (x16)

2002-1292 - Orange Endplate for 2202 (x2)

2210-1201 - Grey 2 conductor DIN-rail terminal with button push-in up to 16mm (x4)

2210-1204 - Blue 2 conductor DIN-rail terminal with button push-in up to 16mm (x4)

2210-1207 - Green/Yellow 2 conductor DIN-rail terminal with button push-in up to 16mm (x4)

2010-1292 - Orange Endplate for 2210 (x2)

#### Technical Specification

Attribute	Value

**9-AC3087-2022-V1**