


3 - Circuit Protection& Industrial Control



Acel part number (AC35121)

RCBO 10A 30mA 10kA

Features and benefits

Type A, B Curve 10kA 750mm neutral lead din rail mounting

Technical Specification	
Attribute	Value
STANDARD	IEC/EN 61009-1
NUMBER OF POLES	1P+N (Switched)
RATED VOLTAGE (Un/AC)	230V
FREQUENCY (Hz)	50/60
RATED BREAKING CAPACITY (Icn)	10000A (10kA)
TRIPPING CHARACTERISTICS	B CURVE : 3-5In, C 5-10IN
RESIDUAL CURRENT CHARACTERISTICS	TYPE A (AC AND PULSATING
RATED RESIDUAL OPERATING CURRENT (IΔn)	0.03
MECHANICAL ENDURANCE	20,000 / 4,000
PROTECTION DEGREE (IP)	20
FLYING NEUTRAL CABLE LENGTH (mm)	750mm
MOUNTING	35mm din rail
MATERIAL	PA6 (Nylon 6)
WEIGHT (1PC) Kg	0.2

3-AC35121-2024-V1



www.electric-center.co.uk

Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.