



| Technical Specification | | | | |
|---|--|--|--|--|
| Power | 14W | | | |
| Construction | Polycarbonate Body and lens | | | |
| Driver | BELL | | | |
| LED Chip | Samsung | | | |
| IP Rating | IP65 | | | |
| Operating Temp | -20°C to +35°C | | | |
| Input Voltage | 220 - 240V | | | |
| Power Factor | > 0.9 | | | |
| CRI | 85 - Exceeds EU standard of Ra 80 for Colour Rendering Index | | | |
| LMR | 80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio | | | |
| Colour Temp | 4000K | | | |
| Lumens | 1500 | | | |
| Energy Savings | 50% | | | |
| Life | 30000 Hours | | | |
| ¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio ² Exceeds EU standard of RA 80 for Colour Rendering Index ³ Subject to terms & conditions | | | | |

| Cod <mark>e</mark> | CCT (K) | Lumens | Description | |
|------------------------|---------------|--------|---|-------|
| AC446 <mark>110</mark> | 4000 | 1500 | 14W LED Bulkhead, White w/Opal Bezel | Round |
| N GUA | aintea | enderi | THE P | |
| 3 3 | 80 | 85 | IP65 | |
| YEAR C | 810* 5 | | Fitting | |
| Standard P | IK8 Pating | |) | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

4_AC446110_2021_V1



www.electric-center.co.uk Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.