









Technical Specification	n	
Сар Туре	LED	
Total Power	6.7	
Lumens (Im)	630	
Beam Angle	60	
Lamp Life (Hrs)	30000	
Number of LEDs	1	
Comparable To	50W LV halogen	
CRI	80	
CCT (K)	3000	
Efficacy (Im/cctW)	94	
Lux at 1m	750	
Power Factor	0.9	
Colour	White	
Cut Out (mm)	72	
Projection (mm)	5	

AC447191

7W IP65 Fire Rated Downlight

- Suitable for domestic dining, living, bathroom and bedroom spaces, hotel & office reception areas
- LED replacement for 50W LV halogen downlights
- LEDchroic lens replicating halogen dichroic with uniform, shadow-free light
- Low glare
- Tested for use with I-Joists & Metal Web Joists
- Complies with BS476 Part 21. Report and certificate from INTERNATIONAL FIRE CONSULTANTS (IFC)
- Designed and tested to retain the integrity of 30, 60 and 90 minute fire rated ceilings compliant with Building Regulations Parts B, C and E
- Shallow profile of only 60mm depth
- Prewired with 0.3m of flex
- Complete with 3-way double push-in connector block allowing loop in loop out
- Chrome and brushed chrome trims available as an accessory
- High efficacy of 94lm/W

4-AC447191-2021-V1

