



AC447192

7W IP65 Fire Rated Downlight

- Suitable for domestic dining, living, bathroom and bedroom spaces, hotel & office reception areas
- LED replacement for 50W LV halogen downlights
- LEDchroic lens replicating halogen dichroic with uniform, shadow-free light
- Low glare
- Tested for use with I-Joists & Metal Web Joists
- Complies with BS476 Part 21. Report and certificate from INTERNATIONAL FIRE CONSULTANTS (IFC)
- Designed and tested to retain the integrity of 30, 60 and 90 minute fire rated ceilings - compliant with Building Regulations Parts B, C and E
- Shallow profile of only 60mm depth
- Prewired with 0.3m of flex
- Complete with 3-way double push-in connector block allowing loop in loop out
- Chrome and brushed chrome trims available as an accessory
- Wide operating ambient temperature range of -20°C to +40°C High efficacy of 99lm/W

Technical Specification

| | |
|--------------------|----------------|
| Cap Type | LED |
| Total Power | 6.7 |
| Lumens (lm) | 660 |
| Beam Angle | 60 |
| Lamp Life (Hrs) | 30000 |
| Number of LEDs | 1 |
| Comparable To | 50W LV halogen |
| CRI | 80 |
| CCT (K) | 4000 |
| Efficacy (lm/cctW) | 99 |
| Lux at 1m | 770 |
| Power Factor | 0.9 |
| Colour | White |
| Cut Out (mm) | 72 |
| Projection (mm) | 5 |

4-AC447192-2021-V1