



4 - Lamps & Lighting







Technical Specification	
Wattage	18w
Lamp Cap	GR10q
Voltage	220-240 Vac 50-60 Hz
Current	90 mA
CCT options	4000k
Nominal Luminous Flux	1800lm
Nominal Lifetime	30,000
Dimmable	Corridor Function (10% Standby Option)
Switching Cycles	50,000
Warm-up time to 60%	Instant full light
Diameter	192x192mm
Rated Peak Candelas	620 cd
Power Factor	0.88
LMF at Nominal Lifetime	0.75
SDCM of CCT	<6
CRI	>83
Start Time	0.39s
Ambient Temperature	
Emergency Module	AC44897 (Standard) and AC44863 (Self-testing)
Detection Range (m)	1-8
Detection Angle	360 degree
Operation time	8sec-30min
Ambient light thresshold	10-2000
Standby Power (w)	1.2
HF System +	5 8GHz

AC44896

18w Sensor DD lamp 4pin 4000k

Features and Benefits:

- Microwave sensor
- Optional 10% dimming corridor function
- For maximum energy savings, bypass all control gearand supply directly from the mains
- Save energy up to 65% compared with a fluorescent lampwith magnetic ballast
- Single side high lumen output for light onlywhere its needed
- Long life of 30,000h
- Compatible with emergency modules (Standard AC44897 and Self-testing AC44863)
- Instant start
- Negligible UV output
- Mercury free

4-AC44896-2021-V1

