



## 4 - Lamps & Lighting



| Ø28mm<br>        |  |  |
|------------------|--|--|
|                  |  |  |
| Length<br>1500mm |  |  |
|                  |  |  |

| Technical Specification                                                                                                                                                             |                                                              |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|--|--|--|
| Power                                                                                                                                                                               | 24W                                                          |  |  |  |
| Сар                                                                                                                                                                                 | G13                                                          |  |  |  |
| Lumens                                                                                                                                                                              | 2200                                                         |  |  |  |
| Energy Savings                                                                                                                                                                      | 59%                                                          |  |  |  |
| Colour Temp                                                                                                                                                                         | 4000K                                                        |  |  |  |
| Dimmable                                                                                                                                                                            | No                                                           |  |  |  |
| Life                                                                                                                                                                                | 25000 Hours                                                  |  |  |  |
| CRI                                                                                                                                                                                 | 85 - Exceeds EU standard of Ra 80 for Colour Rendering Index |  |  |  |
| LMR                                                                                                                                                                                 | 80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio  |  |  |  |
|                                                                                                                                                                                     |                                                              |  |  |  |
|                                                                                                                                                                                     |                                                              |  |  |  |
|                                                                                                                                                                                     |                                                              |  |  |  |
|                                                                                                                                                                                     |                                                              |  |  |  |
|                                                                                                                                                                                     |                                                              |  |  |  |
| <sup>1</sup> Exceeds EU standard of 70 for Lumens Maintenance Ratio <sup>2</sup> Exceeds EU standard of RA 80 for Colour Rendering Index <sup>3</sup> Subject to terms 8 conditions |                                                              |  |  |  |
| •                                                                                                                                                                                   |                                                              |  |  |  |

## AC49186

## **LED T8 Tube**

Our LED T8 tubes are suitable for both switch start and high frequency and are the perfect way to replace conventional fluorescent tubes. A cost-effective energy saving solution without the need to replace a complete fitting while reaping the energy saving benefits of LED.

- Designed to replace conventional fluorescent tubes.
- Long life of 25000 hours
- Low maintenance costs
- 3 Year Guarantee
- Simple Retrofit

| Code                  | CCT (K) | Lumens | Description                                   |
|-----------------------|---------|--------|-----------------------------------------------|
| AC491 <mark>86</mark> | 4000    | 2200   | 24W LED T8 Tube - G <mark>13</mark><br>1500mm |







4\_AC49186\_2021\_V1

