









Technical Specification	Technical Specification				
Power	6.6W				
Сар	ES				
Lumens	810				
Energy Savings	89%				
Colour Temp	2700K				
Dimmable	No				
Life	25000 Hours				
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index				
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio				
<sup>1</sup> Exceeds EU standard of 70 for Lumens Maintenance Ratio <sup>2</sup> Exceeds EU standard of RA 80 for Colour Rendering Index <sup>3</sup> Subject to terms & conditions					

## AC49479

## 110V LED GLS

The 110V LED GLS has been specially designed for safety applications. As a direct replacement for standard GLS, this tough, robust GLS is suitable for site lighting, with a colour coded yellow base for easy identification.

- Suitable for site lighting
- Direct replacement for standard GLS
- Retrofit size
- Suitable for use with low voltage site transformers
- Colour coded yellow base for easy identification
- 89% Energy Saving
- IP65 when used with suitable lamp holder
- Tough, robust design
- Plastic envelope

Code	CCT (K)	Lumens	Description
AC49479	2700	810	6.6W LED 110V GLS ES









4-AC49479-2022-V1

