









| Technical Specification   |  |  |  |
|---|--|--|--|
| Power   | 21W  |  |  |
| Сар   | G13  |  |  |
| Lumens  | 2600   |  |  |
| Energy Savings  | 63%  |  |  |
| Colour Temp   | 4000K  |  |  |
| Dimmable  | No   |  |  |
| Life  | 25000 Hours  |  |  |
| CRI   | 85 - Exceeds EU standard of Ra 80 for Colour Rendering Index |  |  |
| LMR   | 80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
| ¹Exceeds EU standard of 70 for Lumens Maintenance Ratio ²Exceeds EU standard of RA 80 for Colour Rendering Index ³Subject to terms & conditions |  |  |  |

## AC49493 21W LED T8 Tube G13, 4000K, 1500mm

Our LED T8 tubes are suitable for both switch start and high frequency and are the perfect way to replace conventional fluorescent tubes. A cost-effective energy saving solution without the need to replace a complete fitting while reaping the energy saving benefits of LED.

- Designed to replace conventional fluorescent tubes.
- Long life up to 25000 hours
- Low maintenance costs
- 3 Year Guarantee
- 63% Energy Savings
- Simple Retrofit
- Plastic envelope

| Code    | CCT (K) | Lumens | Description                          |
|---------|---------|--------|--------------------------------------|
| AC49493 | 4000    | 2600   | 21W LED T8 Tube - G13, 4000K, 1500mm |







4-AC49493-2022-V1

