



AC5193

BATTERY POWERED MULTI-SENSOR SMOKE ALARM

- Smart RF Ready - Fit a Smart RF Radio Module (AC5223) to wirelessly interlink up to 50 Smart RF products
- Thermoptek Multi-Sensor optical sensing technology as used by over 90% of the UK Fire and Rescue Services
- Intelligent status monitoring without intrusive standby indicator LED
- Easily accessible central button to for Test / Smart Silence / Locate functions
- Smart Silence allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound
- Grade F1 as per BS 5839-6:2019

Technical Specification	
Supply voltage	230V AC, 50Hz
Battery back-up	10 year sealed for life Panasonic lithium
Technology	Thermoptek Multi-Sensor and Smart RF Ready
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Wall / Ceiling
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	Up to 93% RH non-condensing
Plastic material	ABS, UL94 V0 fire retardant
Warranty	5 years
Master pack quantity	10
Weight	150g
Certified to	EN14604:2005+AC:2008
Operating Frequency	868 MHz

5-AC5193-2021-V1