



AC5196

DIGITAL BATTERY POWERED CARBON MONOXIDE ALARM

- Advanced electrochemical sensor calibrated and tested in CO gas.
- 7 year sealed for life lithium battery.
- Unique digital LCD screen.
- The alarm has a built in room temperature indicator with a range of ± 2 degrees.
- Shows the peak levels of CO detected over a 4 week period.
- Can be free-standing or wall mounted.
- Test button - to test circuitry and sounder.
- End of life indication.



BS EN50291-1:2010+A1:2012
BS EN50291-2:2010
Licence No: KM 551504

Technical Specification	
Supply voltage	3V DC
Technology	Advanced electrochemical
Alarm sound level	85dB(A) at 1m (minimum)
Installation positions	Wall / Freestanding
Operating temperature	-10°C to +40°C
Operating humidity	30% to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	30% to 90% RH non-condensing
Plastic material	ABS, UL94 V0 fire retardant
Warranty	7 years
Master pack quantity	5
Weight	118g
Certified to	BS EN50291-1:2010+A1:2012 and BS EN50291-2:2010
For use in	Any room with a fuel burning appliance e.g. boiler, open fires, gas hob or a flue

5-AC5196-2021-V1