



AC5197

BATTERY POWERED CARBON MONOXIDE ALARM

- Smart RF Ready - Fit a Smart RF Radio Module (AC5223) to wirelessly interlink up to 50 Smart RF products
- Advanced electrochemical sensor calibrated and tested in CO gas
- Easily accessible central button - Test / Smart Silence / Locate
- Integrated flip down bracket
- Single pin or 2 screw fitting options
- Optional tamper resistant feature to prevent unauthorised removal
- Sleep Easy - a low battery chirp can be silenced for 8 hours by pressing the test button, this can be used up to 10 times
- Can be wall-mounted or freestanding offering greater flexibility in positioning
- For additional protection, CO alarms may be placed in rooms individuals spend considerable time whilst awake e.g. bedrooms, living rooms

Technical Specification	
Supply voltage	3V DC sealed lithium battery
Technology	Advanced electrochemical and Smart RF Ready
Installation positions	Wall / Freestanding
Operating temperature	-10°C to +40°C
Operating humidity	30% to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	30% to 90% RH non-condensing
Plastic material	UL94 V0 Flame Retardant
Warranty	5 years
Master pack quantity	10
Weight	86g
Certified to	BS EN 50291-1 & 2: 2010
Maximum number of connected units	50 Smart RF devices
For use in	Any room with a fuel burning appliance e.g. boiler, open fires, gas hob or a flue

5-AC5197-2021-V1