

5 - Emergency Lighting, Fire & Safety



Technical Specification	
Operation AC/DC	AC
Battery back-up	9V replaceable battery back-up
Technology	Optical
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Ceiling
Operating temperature	5°C (40°F) to 38°C (100°F)
Operating humidity	10% to 85% relative
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85% relative
Plastic material	ABS, UL94 VO fire retardant
Warranty	5 years
Master pack quantity	10
Certified to	EN 14604: 2005

AC5224

MAINS POWERED SMOKE ALARM + PUSH FIT BASE

- 230V mains powered smoke alarm
- 9V zinc carbon battery back-up
- Modern design style
- Improved Push2fit base for quicker installations
- Optical technology reduces nuisance alarms
- Large central test and silence button makes weekly testing and silencing easy
- LED operating indicators Power, Fault / Alarm
- Low battery warning indicator
- Multi-alarm interconnect up to 12 smoke (AC5224), heat (AC5225) & CO (AC5226) units – when one sounds they all sound
- Safety clip feature, to prevent installation of smoke alarm without battery installed
- 5 year warranty
- EN 14604: 2005

5-AC5224-2021-V1

