

## 5 - Emergency Lighting, Fire & Safety



Technical Specification	
Operation AC/DC	AC
Battery back-up	9V replaceable battery back-up
Technology	Thermistor
Alarm sound level	85dB(A) at 3m (minimum)
Battery Type	9V PP3 zinc carbon
Installation positions	Ceiling
Operating temperature	Class A2 detection : 54°C – 70°C
Operating humidity	10% to 85% relative
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85% relative
Warranty	5 years
Master pack quantity	10
Certified to	BS 5446-2: 2003

## **AC5225**

## MAINS POWERED HEAT ALARM + PUSH FIT BASE

- 230V mains powered heat alarm
- 9V battery back-up
- Modern design style
- Improved Push2fit base for quicker installations
- Ideal for kitchens, attics and garages
- Large central test button
- Separate silence button
- LED operating indicators Power, Fault, Alarm
- Low battery warning indicator
- Multi-alarm interconnect up to 12 smoke (AC5224), heat (AC5225) & CO (AC5226) units – when one sounds they all sound
- Safety clip feature, to prevent installation of alarm without battery installed
- 5 year warranty
- BS 5446-2: 2003

5-AC5225-2021-V1

