

## **5 - Emergency Lighting, Fire & Safety**







Technical Specification	
Light Source	3w SMT LED
IP rating	IP50
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz ± 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	800gm
Battery	LiFePo4 3.2v 1500mAh
Size	344W x 237H X 42mmD (Excludes brackets)
Viewing distance	30m

## AC55714

# 5-IN-1 Emergency Exit Sign

The 5-in-1 emergency exit sign means you will always have the correct mounting method.

The 5-in-1 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

#### **Features**

- 5 Mounting options supplied as standard
- Wall
- Ceiling
- Flag
- Recessed
- Suspended
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates LiFePo4 3.2v 1500mAh battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards

### **Remote Control Option**

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to  $7 \mathrm{m}$ 

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.

Press once for 5 second monthly test Press twice for 3 hour yearly test LED confirms pass/fail status

5-AC55714-2024-V1

