



AC5679

Emergency Bulkhead

The AC5679 is a 3 watt maintained/non-maintained environmentally friendly emergency bulkhead. The AC5679 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

Features

- Long life LED technology
- Remote control testing option
- Maintained / Non-maintained operation
- Can be ceiling or wall mounted
- Sleek and minimalistic design
- Optically enhanced diffuser
- Polycarbonate construction
- Lightweight and easy to install
- NiCd battery
- Double sided blade exit sign - AC5698
- Semi-recessing kit available - AC5699
- Low environmental impact & running costs
- Meets BS EN 60598-1:2008 and other relevant standards
- IP65 weatherproof
- 185lm Maintained Output 108Lm emergency output
- Hinged gear tray
- 20mm conduit entry

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to 7m



Technical Specification

Light Source	3w SMT LED
IP rating	IP65
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz ± 10%
Mains current	(Max) 50mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	0 TO 40 °C
Weight	700gm
Battery	3.6v 1500mAH Nickel cadmium
Lumen output	185lm (maintained) 108lm (emergency)



5-AC5679-2021-V1