



AC5681

Emergency Bulkhead

The AC5681 is a 7.3 watt maintained/non-maintained emergency bulkhead. The AC5681 is supplied with a full legend set. The high lumen output ensures it meets the requirements of most applications. The AC5681 is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

Features

- Long life LED technology
- Remote control testing option
- Maintained / Non-maintained operation
- Can be ceiling or wall mounted
- Sleek and minimalistic design
- Optically enhanced diffuser
- Polycarbonate construction
- Lightweight and easy to install
- NiCd battery
- Legend Kit - AC5682
- Low environmental impact & running costs
- Meets BS EN 60598-1:2008 and other relevant standards
- IP65 weatherproof
- 185lm Maintained Output 108Lm emergency output
- Hinged gear tray
- 20mm conduit entry

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittinas can be tested from up to 7m



Technical Specification

| | |
|--------------------|---|
| Light Source | 3w SMT LED |
| IP rating | IP65 |
| Emergency Duration | 3-Hours (minimum) |
| Mains voltage | 230v 50Hz ± 10% |
| Mains current | (Max) 50mA 35mA quiescent |
| Recharge period | Less than 24 hours |
| Charge indicator | Integral Green LED |
| Changeover voltage | As per requirements of BS EN 60598-2-22 |
| Temperature range | 0 TO 40 °C |
| Weight | 950gm |
| Battery | 3.6v 2000mAH Nickel cadmium |
| Lumen output | 320lm (maintained) 210lm (emergency) |
| | |
| | |
| | |



5-AC5681-2021-V1