



Technical Specification	
Housing material	Polycarbonate / Aluminium
Standard colour	White RAL 9003 + Silver
Printing foil	Silk screen
Viewing Distance	28m & 26m (recessed)
Illuminant	16x LED - white
Protection category	IP40
Supply voltage	230V 50Hz ± 10%
Battery	3.6V 900mAh NiCd
Operating temperature	0 - +55°C (Non Condensing)
Weight	0.8Kg
Viewing distance	28m
netting distance	

## AC5686

## Flush Exit Sign

The ultra slim-line AC5686 LED emergency exit sign range offering hanging, recessed, flush mounted and wall/ ceiling mounted versions.

## Features

Comprehensive family, comprising hanging, recessed, hanging recessed and wall/ceiling mounted versions

Stylish ultra slim-line and compact range of LED exit signs complete with full set of pictograms

3 hour maintained Long life LED technology

Sleek unobtrusive design with aluminium LED sign extension and polycarbonate gear housing

Viewing distances of 28m and 26m (recessed version only)

Push to test function (excluding wall mounted version)

Adjustable suspension heights available on hanging exit signs

The AC5686 allows the fitting to be recessed in to a ceiling giving a sleek appearance.

Meets BS EN 60598-2-22 and other relevant standards



+



## www.electric-center.co.uk

Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.