



AC5713

Emergency Bulkhead

The AC5713 is a 3 watt maintained/non-maintained environmentally friendly emergency bulkhead. The AC5713 gives 150lm in the emergency mode and along with the IP65 rating this ensures it is suitable for most applications. The inbuilt green charge LED gives great visibility of the charging state of the fitting.

Features

- Long life LED technology
- Maintained / Non-maintained operation
- Can be ceiling or wall mounted
- Comes with Pictogram Pack
- Sleek and minimalistic design
- Optically enhanced diffuser
- Polycarbonate construction
- Lightweight and easy to install
- NiCd battery
- Semi-recessing kit available
- Low environmental impact & running costs
- Meets BS EN 60598-1:2008 and other relevant standards
- IP65 weatherproof
- 150 lm emergency output
- Hinged screwless gear tray
- 16mm or 20mm conduit entry

Technical Specification

Light Source	3w SMT LED
IP rating	IP65
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz \pm 10%
Mains current	(Max) 50mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	0 TO 40 °C
Weight	320gm
Battery	3.6v 1500mAH Nickel cadmium
Lumen output	150Lm

5-AC5713-2021-V1