



6 - Ventilation & Heating





Technical Specification	
Power Output:	8.5kW
Temperature Control:	Accurate to ±1.5°C
Start-up Temperature:	43°C
Temperature Selection:	25 to 47°C
Current Rating:	35.41 Amps
Operating Pressure:	1 to 10bar (15 to 150 psi)
Min. Floe Rate:	1 I/min.
Water Connection:	15mm compression or push-fit
IP Rating:	IPX4
Approvals:	BEAB (CE Marked)
ErP Class Rating:	A
Energy Efficiency:	39%
Energy Consumption:	478 kWh/A

AC6093

Glow-Thermo. 8.5kW Shower

- Accurate temperature control to within 1.5°C for a comfortable and safe shower experience
- All tactile push button controls with audible confirmation of settings adjustment for ease of operation
- Large LED digital temperature display
- Phased shutdown safety protection for next user and heating element scale protection
- Temperature Limiter lock option set at installation
- SmartFit Technology with multi-entry options for water and power connection, ideal for replacement installations
- Five spray-mode shower head with easy rub-clear nozzles
- 600mm high chrome riser rail with variable position top wall bracket fixing for ease of retrofit
- 1.5 metre long anti-kink flexible shower hose
- Push button handset clamp to adjust height and shower head angle to suit all users
- 3 year UK guarantee

6-AC6093-2021-V1

