

Image coming soon   Cuiet Fans - Zone 1 - 100mm     Image coming soon   Low energy motor with a maximum consumption of 7 Watts. Low SFP of just 0.33W//s. Complete with integral backraught shutters. Complete with a struction rate whilst producing an incredibly quiet running volume all with the additional flexibility of being IPX5 compliant. IEE Regulations (U.K.) and wor IPX5 fans to be installed into zone 1 without the need for low voltage transformer making this comprehensive range ideal for Bathrooms and toilets. The unit also comes complete with a performance enhancing turning value system located in the spigot to improve performance by maintaining a high utput.     Nuters   Spring refum     Speed (Ird)   20.8     Waranty   3yr     Weight (kg)   0.821			AC6349
Image coming soonconsumption of 7 Watts. Low SFP of just 0.33W/l/s. Complete with integral backdraught shutters. Complies with both Part F & LThe Quiet Fan is the latest in domestic ventilation to incorporate a high extraction rate whilst producing an incredibly quiet running volume all with the additional flexibility of being IPX5 compliant. IEE Regulations (U.K.) allow for IPX5 fans to be installed into zone 1 without the need for low voltage transformer making this comprehensive range ideal for Bathrooms and toilets.Technical Specification Adjustable Timer YesThe unit also comes complete with a performance enhancing turning vane system located in the spigot to improve performance by maintaining a high output.The Unit also comes complete with a performance by maintaining a high output.Forlie Standard Boutor TypeSpeed (Irs) Speed (Irs) Speed (Irs) Spigot Dia (mm) 100 Timer Max (min) 20 WarrantyWarranty SyrBoth Control TypeKarrantySyrBoth Control TypeBoth Control TypeExtendion Speed (Irs) SyrBoth Control TypeExtend	Image coming soon		·
Technical Specificationventilation to incorporate a high extraction rate whilst producing an incredibly quiet running volume all with the additional flexibility of being IPX5 compliant. IEE Regulations (U.K.) allow for IPX5 fans to be installed into zone 1 without the need for low voltage transformer making this comprehensive range ideal for Bathrooms and toilets.M(mm)163H (mm)163H (mm)163Input Power 1 (W)7Installation TypeWall, Panel, CeilingModeIntermittentProfileStandardSpeed Control TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yr6-Ac6349-2021-v1			consumption of 7 Watts. Low SFP of just 0.33W/I/s. Complete with integral backdraught shutters. Complies with
Technical SpecificationYestransformer making this comprehensive range ideal for Bathrooms and toilets.Adjustable TimerYesransformer making this comprehensive range ideal for Bathrooms and toilets.W (mm)163the unit also comes complete with a performance enhancing turning vane system located in the spigot to improve performance by maintaining a high output.Installation TypeWall, Panel, Ceilingthe unit also comes complete with a performance enhancing turning vane system located in the spigot to improve performance by maintaining a high output.ProfileStandardSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yrBathroom, En Suite			ventilation to incorporate a high extraction rate whilst producing an incredibly quiet running volume all with the additional flexibility of being IPX5 compliant. IEE Regulations (U.K.) allow for IPX5 fans to be installed into zone 1 without the need for low voltage
Adjustable TimerYestransformer making this comprehensive range ideal for Bathrooms and toilets.W (mm)163transformer making this comprehensive range ideal for Bathrooms and toilets.H (mm)163transformer making this comprehensive range ideal for Bathrooms and toilets.Input Power 1 (W)7transformer making this comprehensive range ideal for Bathrooms and toilets.Installation TypeWall, Panel, Ceilingthe unit also comes complete with a performance enhancing turning vane system located in the spigot to improve performance by maintaining a high output.ProfileStandardthe unit also comes complete with a performance enhancing turning vane system located in the spigot to improve performance by maintaining a high output.ShuttersSpring returnSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yr6-Ac6349-2021-v1	Technical Specification		
W (mm)163H (mm)163Input Power 1 (W)7Installation TypeWall, Panel, CeilingModeIntermittentProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpigot Dia (mm)100Timer Max (min)20Warranty3yr6-AC6349-2021-v1	· · · · · · · · · · · · · · · · · · ·	Yes	•
Input Power 1 (W)7Installation TypeWall, Panel, CeilingModeIntermittentProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yr	W (mm)	163	range ideal for Datilioonis and tollets.
Input Power 1 (W)7Installation TypeWall, Panel, CeilingModeIntermittentProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yr		163	The unit also comes complete with a
ModeIntermittentProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yrBathroom, En Suite	Input Power 1 (W)	7	•
ModeInternitientProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yrBathroom, En Suite	Installation Type	Wall, Panel, Ceiling	performance by maintaining a high
ProfileStandardRoom TypeBathroom, En SuiteShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yrG-AC6349-2021-v1	Mode	Intermittent	
ShuttersSpring returnSpeed Control TypeExternal, On/OffSpeed (I/s)20.8Spigot Dia (mm)100Timer Max (min)20Warranty3yrG-AC6349-2021-v1	Profile	Standard	output.
Speed Control Type External, On/Off   Speed (I/s) 20.8   Spigot Dia (mm) 100   Timer Max (min) 20   Warranty 3yr	Room Type	Bathroom, En Suite	
Speed (I/s) 20.8   Spigot Dia (mm) 100   Timer Max (min) 20   Warranty 3yr	Shutters	Spring return	
Spigot Dia (mm) 100   Timer Max (min) 20   Warranty 3yr   6-AC6349-2021-v1	Speed Control Type	External, On/Off	
Timer Max (min) 20   Warranty 3yr   6-AC6349-2021-v1	Speed (I/s)	20.8	
Warranty 3yr 6-AC6349-2021-v1	Spigot Dia (mm)	100	
0-AC0349-2021-VI	Timer Max (min)	20	
	Warranty	3yr	6-AC6349-2021-v1
	Weight (kg)	0.621	



www.electric-center.co.uk