



AC66292

200W 3mm Undertile heating cable with Primer

A professional great value cable system designed to offer a cost effective heating solution for projects without sacrificing the quality of the product.

This zero maintenance heating system is designed to provide sole source heating in properties insulated to the current building regulations and it can be used beneath virtually any floor type if covered with a leveling compound.

Mix and match with other cable sizes to provide the perfect coverage whatever the size of your room.

Fit directly beneath tiles or stone flooring with up to 230W/m² output. Space the cables to give 160W/m² and cover with a levelling compound for use beneath other floor coverings such as carpet, vinyl, laminate and wood.

| Technical Specification | |
|-------------------------|---|
| Cable Length | 11.8m |
| Output | 200W |
| Loading | 0.9 Amps |
| Resistance | 270 Ohms |
| Maximum Cable Load | 17W/metre |
| Coldtail Lead | 2m double insulated fully earthed cable |
| Wire Thickness | 2.7 - 3.2mm |
| Cable Flexibility | Minimum bend radius 18mm |
| Inner Insulation | Fluoropolymer (FEPY7) 200°C |
| Outer Insulation | Mechanical protection from PVC(Y) 90°C |
| Earth Protection | 100% aluminium earth shield |
| Manufactured In | Denmark |
| Approvals | BEAB, UKCA, SEMKO, CE, IPX7, EMC Safe |
| Approved To | EN 60335-1:1998, EN60335-2-17:1999, IEC 60730 |
| Compliant With | Part L, 18 th Edition IEE Wiring Regulations |

- Ideal for use in complicated rooms
- Supplied with double sided tape
- Advanced dual conductor cable design
- Suitable for almost any floor covering
- Use directly beneath tile and stone floors
- Cover with compound for carpet and wood floors
- Quick and easy to install
- Insulative primer helps prevent downward heat loss
- 3mm cable for ultra-low build height
- Cost effective, great value and flexible option
- 10 Year Warranty

6-AC66292-2021-V1